

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property  
Organization  
International Bureau



(43) International Publication Date  
8 January 2004 (08.01.2004)

PCT

(10) International Publication Number  
**WO 2004/004390 A1**

(51) International Patent Classification<sup>7</sup>: **H04Q 7/34, 7/22**

(21) International Application Number:

PCT/SE2003/001117

(22) International Filing Date: 26 June 2003 (26.06.2003)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:

0202003-0 26 June 2002 (26.06.2002) SE

(71) Applicant (for all designated States except US):  
**SYNAPSE SYSTEMS AB** [SE/SE]; Urban Hjärnes  
väg 14, S-168 58 Bromma (SE).

(72) Inventor; and

(75) Inventor/Applicant (for US only): **BERGQVIST, Per**  
[SE/SE]; Urban Hjärnes väg 14, S-168 58 Bromma (SE).

(74) Agents: **ASKERBERG, Fredrik** et al.; Groth & Co. KB,  
Box 6107, S-102 32 Stockholm (SE).

(81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.


(84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Declarations under Rule 4.17:

— as to applicant's entitlement to apply for and be granted a patent (Rule 4.17(ii)) for the following designations AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH,

[Continued on next page]

(54) Title: A METHOD FOR THE AUTOMATIC MANAGEMENT OF TERMINAL-DEPENDENT INFORMATION



(57) Abstract: The present invention concerns a method of the automatic management of terminal-dependent information in a wireless communication system. The method comprises the steps:- the detection of the unique identity for the terminal that the subscriber is currently using;- the adaptation of information for the type of terminal detected; and-the presentation of the adapted information on the said terminal.

WO 2004/004390 A1



CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, UZ, VC, VN, YU, ZA, ZM, ZW, ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR,

GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG)

— of inventorship (Rule 4.17(iv)) for US only

**Published:**

— with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

**A METHOD FOR THE AUTOMATIC MANAGEMENT OF TERMINAL-  
DEPENDENT INFORMATION**

10/518296

DT01 Rec'd PCT/PTC 16 DEC 2004

Technical Area

5           The present invention concerns, according to a first aspect, a method for the automatic management of terminal-dependent information in a wireless communication network.

          According to a second aspect, the present invention concerns at least one software product for the automatic management of information in a wireless  
10   communication network.

Background to the Invention

          Mobile terminals are managed in wireless communication systems such as GSM and UMTS. These terminals satisfy the standards that are required in  
15   order to be approved in the communication system, but an ever-increasing part of the functionality is of such a nature that it is either not standardised at all, or at least not standardised in a unified manner. Furthermore, the terminals have different properties with respect to the ability to present information and with respect to the set of services built into the terminal.

20           Certain parts of the settings relating to services are stored on SIM cards. It is possible for an operator to influence these before the subscription is purchased. The operator cannot normally influence the settings that are stored in the memory of the terminal before the subscriber has purchased the terminal (unless the terminal is intimately packaged with a certain specified subscription).

25           Furthermore, subscribers change terminals while keeping an existing subscription. It is possible that the new terminal does not have the same abilities as the previous terminal.

          Manual configuration of services is generally currently required in order for these to be adapted to a particular type of terminal.

30           This is often experienced as complicated by many users, and it is considered to be a contributory factor to the fact that certain services are seldom or never used. It is obvious that this is a significant disadvantage with existing solutions.

Each mobile unit in a wireless communication network such as GSM or UMTS has a unique identity. The terminal itself is aware of this identity and it is primarily intended to be used as theft-protection. The network can request the identity from the terminal during communication with the network before further communication is permitted.

This terminal identity, IMEI, contains information about the manufacturer, model number, serial number and, in certain cases, also the current version of software.

There is currently no possibility for an external service (that is, a service outside of BSC/RNC/MSC/SGSN) to request this identity.

### Summary of the Invention

One part of the invention has the purpose of making this identity known to external services on request. The invention describes a number of possible methods for collecting information about the terminal identity.

It is possible that it is undesirable for security reasons to expose the exact information concerning which unique terminal that is being used, and thus general information in the form of properties such as, for example, the model number are generated. The operator can choose, in order to increase the security further, to publish only generic subservices which means that the current terminal of the subscriber never leaves the domain of the operator.

By correlating the identity of the terminal with information that is available in advance concerning the properties of different models, it is possible with the aid of the invention to present information about properties to services, which can automatically adapt information for the relevant terminal.

It is the intention of the present invention to solve the problems described above. This is achieved according to a first aspect with a method for the automatic management of terminal-dependent information in a wireless communication network as specified in claim 1. The method comprises the following steps:

- the detection of the unique identity for the terminal that the subscriber is currently using;
- the adaptation of information for the type of terminal detected; and
- the presentation of the adapted information on the said terminal.

The need for manual configuration of services such that they are adapted to a certain type of terminal is reduced or eliminated with this method.

A further advantage of the method is that registration of the terminal type used can be made in a database. This database can be used for tailored information for

5 users with a particular type of terminal.

A further advantage of the method is that it makes it possible to generate stimuli for external services during the exchange of terminal used by a subscriber.

Furthermore, the method makes possible automatic migration of service profiles when the subscriber exchanges the terminal.

10 A further advantage in this context is obtained if the step of detecting the type of terminal takes place through monitoring and probing signal links.

A further advantage in this context is obtained if the step of detecting the type of terminal takes place through monitoring and probing signal links for the detection of MSISDN-IMSI mapping.

15 A further advantage in this context is obtained if the method also comprises the steps:

- the request by the user of a service via SMS/USSD or conversation;
- the exchange of IMEI information between MSC and BSC/RNC or between SGSN and BSC/RNC for the subscriber;
- 20 - the capture of current IMEI information about the subscriber by probing the signal link;
- the detection by an application server of the request;
- the request by the application server for terminal properties from the configuration server;
- 25 - the discovery by the configuration server of a unique subscriber identity either by reading information that is stored locally or by a request to HLR.
- the reading by the configuration server of stored IMEI for the subscriber;
- the remapping by the configuration server of IMEI to properties;
- the return by the configuration server of the properties to the application
- 30 server; and
- the transmission of a terminal-dependent configuration to the terminal via SMS or other information channel.

According to one embodiment, a further advantage is obtained if the method further comprises the steps:

- the request by the user of a service via SMS/USSD or conversation;
- the detection by an application server of the request;
- the request by the application server for properties;
- the request by the configuration server for IMEI via modified ATI or a new operation involving HLR.
- 5     - the request by HLR to the terminal for IMEI via MSC/SGSN;
- the remapping by the configuration server of IMEI to properties;
- the return by the configuration server of the properties to the application server; and
- 10    - the transmission of a terminal-dependent configuration to the terminal via SMS or other information channel.

A further advantage is obtained in this context if the step in which HLR requests IMEI from the terminal occurs in two steps:

- the request by HLR to MSC/SGSN for IMEI for the subscriber; and
- 15    - the request by MSC/SGSN to the terminal for IMEI for the subscriber via BSC.

A further advantage is obtained according to one embodiment if the method also comprises the steps:

- the request by the application server for properties from the configuration server;
- 20    - the discovery by the configuration server of the unique subscriber identity either by reading information that is stored locally or by an enquiry to HLR;
- the reading by the configuration server of stored IMEI for the subscriber;
- the contact by the configuration server to collaborating configuration servers if the IMEI information is not present in the local database, whereby the relevant collaborating configuration servers are determined by a request to
- 25    HLR;
- the remapping by the configuration server of IMEI to properties;
- the conversion by the application server of terminal-independent information to terminal-dependent information; and
- 30    - the delivery of terminal-dependent information to the terminal.

A further advantage is obtained in this context if the conversion step takes place based on attributes in the properties.

A second intention of the present invention is to accomplish at least one software product that can be directly loaded into the internal memory of at least one digital computer. The software product, at least one such, comprises software modules in order to carry out the steps according to the method according to the present invention, where the said product or products are run on the said computer, at least one such.

The need for manual configuration of services in order for these to be suitable for a certain type of terminal is reduced or eliminated with this product or products.

A further advantage of the software product is that the registration of the terminal type used can be made in a database. This database can be used for tailored information for users of a certain type of terminal.

A further advantage of the software product is that it makes it possible to generate stimuli to an external service on the exchange of a terminal by a subscriber.

Furthermore, the software product makes automatic migration of service profiles possible when the subscriber exchanges the terminal.

It should be pointed out that when the terms "comprises/comprising" are used in this description, it should be taken to mean the presence of the specified properties, steps or components, but it does not exclude the presence of one or more further properties, parts, steps, components or groups of these.

The embodiments of the invention will now be described with reference to the attached drawings, where:

#### Brief Description of the Drawings

- Figure 1 shows a block diagram of a wireless communication network that can be used to carry out the method according to the present invention;
- Figure 2 shows a block diagram of a second embodiment of a wireless communication network that can be used to carry out the method according to the present invention;
- Figure 3 shows a flow diagram of a first embodiment of a method for the automatic management of terminal-dependent information according to the present invention;

- Figure 4 shows a flow diagram of a second embodiment of the method according to the present invention;
- Figure 5 shows a flow diagram of a third embodiment of the method according to the present invention;
- 5 Figure 6 shows a flow diagram of a fourth embodiment of the method according to the present invention; and
- Figure 7 shows a schematic diagram of some software products according to the present invention.

#### 10 Detailed Description of Embodiments

A list of abbreviations that are used in this description is given below in order to facilitate understanding of the present invention.

##### Abbreviations

15	HLR	Home Location Register
	MSC	Mobile Services Switching Centre
	SGSN	Service GPRS Support Node
	BSC	Base Station Controller
	RNC	Radio Network Controller
20	SMS	Short Message Service
	USSD	Unstructured Supplementary Service Data
	IMEI	International Mobile Equipment Identity
	MSISDN	Mobile Subscriber International Subscriber Directory Number
	IMSI	International Mobile Subscriber Identity
25	SIM	Subscriber Identity Module
	SIM-AT	Subscriber Identity Module – Application Toolkit
	UMTS	Universal Mobile Telephony System
	SMSC	Short Message Service Centre
	VLR	Visitor Location Register

30

Figure 1 shows a wireless communication network 10, which network can be used for execution of the method according to the present invention. The mobile terminal is denoted in Figure 1 by the reference number 12. The wireless communication network 10 comprises a SGSN-node 14, a BSC/RNC-centre 18



connected to the SGSN-node 14, and an MSC-centre 16 connected to the BSC/RNC-centre 18. The communication network 10 further comprises an SMSC-centre 26 connected to the MSC-centre 16. The communication network 10 further comprises an application server 24 connected to the SMSC-centre 26 and a  
5 telephone exchange 22 connected to the MSC-centre 16 and to the application server 24. The communication network 10 further comprises an configuration server 20 connected to the application server 24. The communication network further comprises an HLR-database 30 connected to the application server 24 and to the SGSN-node 14. Finally, the network 10 comprises two probes 28<sub>1</sub>, 28<sub>2</sub>  
10 in order to monitor and probe signal links. These probes 28<sub>1</sub>, 28<sub>2</sub> are connected to the configuration server 20.

Several configuration servers 20 can be connected together, although this is not shown in Figure 1. If information about a subscriber is not present in the centre to which the application makes its request, the correct configuration server  
15 20 can be found with the aid of ATI. The request is made from one configuration server to another using a new protocol.

Figure 2 shows a block diagram of a second embodiment of the communication network shown in Figure 1. Similar components have been denoted in the communication network 40 using the same reference numbers as  
20 those used in Figure 1. These components will not be described further. This network 40 further comprises an HLR database 30 connected to the application server 24 and to the SGSN-node 14. As Figure 2 makes clear, no probes are included in this embodiment.

It should be pointed out that several of the nodes shown in Figure 1 and  
25 Figure 2 are optional, and these are not obligatory in order to carry out the method according to the present invention. The obligatory nodes are the BSC/RNC-centre 18, the MSC-centre 16 and the HLR-database 30.

Figure 3 shows a flow diagram of a method for the automatic management of terminal-dependent information in a wireless network. The method starts at  
30 block 50. The method then continues, via block 52, with the step of detecting the type of terminal that the subscriber is currently using. The method then continues, at block 54, with the step of adapting information to the type of terminal detected. The method then continues, at block 56, with the step of presenting the adapted information on the said terminal. The method terminates at block 58.

Figure 4 shows a flow diagram of a further step included in a first variant of the method shown in Figure 3. The method starts at block 60. The method then continues, at block 62, with the step of the user requesting a service via SMS/USSD or conversation. The method then continues, at block 64, with the step of exchanging IMEI information between MSC and BSC/RNC or between SGSN and BSC/RNC for the subscriber. The method then continues, at block 66, with the step of capturing current IMEI information about the subscriber through probing signal links. The method then continues, at block 68, with the step of an application server detecting the request. The method then continues, at block 70, with the step of the application server requesting terminal properties from the configuration server. The method then continues, at block 71, with the step of the configuration server discovering the unique subscriber identity either by reading information that is stored locally or by a request to HLR. The method then continues, at block 72, with the step of the configuration server reading the stored IMEI for the subscriber. The method then continues, at block 73, with the step of the configuration server remapping the IMEI to properties. The method then continues, at block 74, with the step of the configuration server returning properties to the application server. The method then continues, at block 76, with the step of sending terminal-dependent configuration to the terminal via SMS or another information channel. The method then terminates at block 78.

Figure 5 shows a flow diagram of a further step included in a second variant of the method shown in Figure 3. The method starts at block 80. The method then continues, at block 82, with the step of the user requesting a service via SMS/USSD or conversation. The method then continues, at block 84, with the step of the application server detecting the request. The method then continues, at block 86, with the request by the application server for properties. The method then continues, at block 88, with the step of the configuration server requesting IMEI via a modified ATI or via a new operation involving the HLR. The method then continues, at block 90, with the step of the HLR requesting IMEI from the terminal via MSC/SGSN. The method then continues, at block 92, with the step of the configuration server remapping the IMEI to properties. The method then continues, at block 94, with the step of the configuration server returning properties to the application server. The method then continues, at block 96, with

the step of sending terminal-dependent configuration to the terminal via SMS or another information channel. The method then terminates at block 98.

Figure 6 shows a flow diagram of further steps included in a third variant of the method shown in Figure 3. The method starts at block 110. The method then  
5 continues, at block 111, with the step of the application server requesting properties from the configuration server. The method then continues, at block 112, with the step of the configuration server discovering a unique subscriber identity either by reading information that is stored locally or by a request to HLR. The method then continues, at block 114, with the step of the configuration server  
10 reading stored IMEI for the subscriber. The method then continues at block 115, with the step of the configuration server contacting collaborating configuration servers if IMEI information is not present in the local database, whereby the relevant collaborating configuration servers are determined through a request to HLR. The method then continues, at block 116, with the step of the configuration  
15 server remapping the IMEI to properties. The method then continues, at block 118, with the step of the application server converting terminal-independent information to terminal-dependent information. The method then continues, at block 120, with the step of delivering terminal-dependent information to the terminal. The method terminates at block 122.

20 Figure 7 shows a schematic diagram of some software products according to the present invention. A total of  $n$  different software products,  $102_1, \dots, 102_n$ , are shown in Figure 7, where  $n$  is an integer. The software products  $102_1, \dots, 102_n$ , can be directly loaded into the internal memory of at least one digital computer  $100_1, \dots, 100_n$ . Figure 7 also shows a total of  $n$  computers. Each software product  
25  $102_1, \dots, 102_n$  comprises software modules in order to carry out one part of or all of the steps according to Figure 3 when the product or products  $102_1, \dots, 102_n$ , are run on the computer or computers  $100_1, \dots, 100_n$ . The software products  $102_1, \dots, 102_n$  may, for example, be in the form of diskettes, RAM-disks, magnetic tapes, optomagnetic disks or any other suitable products.

30 The invention is not limited to the embodiments described above. It will be clear that many different modifications are possible within the scope of the attached claims.

---

## CLAIMS

1. A method for the automatic management of terminal-dependent information in a wireless communication network, which method comprises the  
5 steps:
  - the detection of the unique identity of the terminal that the subscriber is currently using;
  - the remapping of the unique identity to properties, including type of terminal
  - the adaptation of information about properties to services for the type of  
10 terminal detected; and
  - the presentation of the adapted information on the said terminal.
2. A method for the automatic management of terminal-dependent information in a wireless communication network according to claim 1,  
15 **characterised by** the step of detecting the type of terminal being carried out by monitoring and probing signal links.
3. A method for the automatic management of terminal-dependent information in a wireless communication network according to claim 1,  
20 **characterised by** the step of detecting the type of terminal being carried out by monitoring and probing signal links in order to detect MSISDN-IMSI mapping.
4. A method for the automatic management of terminal-dependent information in a wireless communication network according to either of claims 1 or  
25 2, **characterised by** the method further comprising the steps:
  - the request by the user of a service via SMS/USSD or conversation;
  - the exchange of IMEI information between MSC and BSC/RNC or between SGSN and BSC/RNC for the subscriber;
  - the capture of current IMEI information about the subscriber by probing the  
30 signal link;
  - the detection by an application server of the request;
  - the request by the application server for terminal properties from the configuration server;

- the discovery by the configuration server of a unique subscriber identity either by reading information that is stored locally or by a request to HLR.
- the reading by the configuration server of stored IMEI for the subscriber;
- the remapping by the configuration server of IMEI to properties;
- 5    - the return by the configuration server of the properties to the application server; and
- the transmission of a terminal-dependent configuration to the terminal via SMS or other information channel.

10    5.        A method for the automatic management of terminal-dependent information in a wireless communication network according to claim 1,

**characterised by** the method further comprising the steps:

- the request by the user of a service via SMS/USSD or conversation;
- the detection by an application server of the request;
- 15    - the request by the application server for properties;
- the request by the configuration server for IMEI via modified ATI or a new operation involving HLR.
- the request by HLR to the terminal for IMEI via MSC/SGSN;
- the remapping by the configuration server of IMEI to properties;
- 20    - the return by the configuration server of the properties to the application server; and
- the transmission of a terminal-dependent configuration to the terminal via SMS or other information channel.

25    6.        A method for the automatic management of terminal-dependent information in a wireless communication network according to claim 5,

**characterised by** the step in which HLR requests IMEI from the terminal occurring in two steps:

- the request by HLR to MSC/SGSN for IMEI for the subscriber; and
- 30    - the request by MSC/SGSN to the terminal for IMEI for the subscriber via BSC.

7. A method for the automatic management of terminal-dependent information in a wireless communication network according to claim 1,

**characterised by** the method further comprising the steps:

- 5       - the request by the application server for properties from the configuration server;
- the discovery by the configuration server of the unique subscriber identity either by reading information that is stored locally or by a request to HLR;
- the reading by the configuration server of stored IMEI for the subscriber;
- 10       - the contact by the configuration server to collaborating configuration servers if the IMEI information is not present in the local database, whereby the relevant collaborating configuration servers are determined by a request to HLR;
- the remapping by the configuration server of IMEI to properties;
- 15       - the conversion by the application server of terminal-independent information to terminal-dependent information; and
- the delivery of terminal-dependent information to the terminal.

8. A method for the automatic management of terminal-dependent information in a wireless communication network according to claim 7,

20       **characterised by** the conversion step occurring based on attributes in the properties.

9. At least one software product ( $102_1, \dots, 102_n$ ) that can be loaded directly into the internal memory of at least one digital computer ( $100_1, \dots, 100_n$ )

25       comprising software modules for carrying out the steps according to claim 1 when the said products, at least one such, ( $102_1, \dots, 102_n$ ) is run on the said computers, at least one such ( $100_1, \dots, 100_n$ ).

---

10/518296




Fig. 1

10/518296




Fig. 2






Fig. 3




Fig. 4

10/518296




Fig. 5




Fig. 6




Fig. 7

## INTERNATIONAL SEARCH REPORT

International application No.

PCT/SE 03/01117

## A. CLASSIFICATION OF SUBJECT MATTER

IPC7: H04Q 7/34, H04Q 7/22

According to International Patent Classification (IPC) or to both national classification and IPC

## B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC7: H04Q, H04L

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

SE,DK,FI,NO classes as above

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

## C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	WO 0163898 A (NORTEL NETWORKS LTD), 30 August 2001 (30.08.01), page 3, line 5 - page 5, line 5 --	1-9
A	WO 0103402 A1 (NOKIA COMMUNICATIONS OY), 11 January 2001 (11.01.01), figure 1, abstract --	1-9
A	WO 0167679 A1 (SHENZHEN LIMING NETWORK SYSTEMS CO, LTD), 13 Sept 2001 (13.09.01), abstract --	1-9
A	WO 0217567 A2 (YOGOGO LTD), 28 February 2002 (28.02.02), abstract -- -----	1-9

☐ Further documents are listed in the continuation of Box C.☒ See patent family annex.

\* Special categories of cited documents:

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier application or patent but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance: the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance: the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art

"&amp;" document member of the same patent family

Date of the actual completion of the international search

5 Sept 2003

Date of mailing of the international search report

10-09-2003

Name and mailing address of the ISA/  
Swedish Patent Office  
Box 5055, S-102 42 STOCKHOLM  
Facsimile No. +46 8 666 02 86

Authorized officer

Stefan Hansson /LR  
Telephone No. +46 8 782 25 00

## INTERNATIONAL SEARCH REPORT

International application No.

PCT/SE 03/01117

Patent document cited in search report			Publication date	Patent family member(s)		Publication date
WO	0163898	A	30/08/01	AU	3217101 A	03/09/01
				CN	1423889 T	11/06/03
				EP	1262055 A	04/12/02
				US	2001043577 A	22/11/01
-----						
WO	0103402	A1	11/01/01	AU	5280299 A	22/01/01
				EP	1198941 A	24/04/02
				JP	2003503803 T	28/01/03
-----						
WO	0167679	A1	13/09/01	AU	3142800 A	17/09/01
				US	2003081617 A	01/05/03
-----						
WO	0217567	A2	28/02/02	AU	8418201 A	04/03/02
				EP	1329056 A	23/07/03
				GB	0021067 D	00/00/00
				GB	0208460 D	00/00/00
				GB	2370951 A	10/07/02
-----						